

Door Energy Performance Ratings



GLASS CRAFT
DOOR COMPANY

www.gcdoor.com

Entrance Door
CPD # GDC-M-3
Wood Door

ENERGY PERFORMANCE RATINGS

PRODUCT DESCRIPTION* Default Frame ** Wood	U-Factor / Solar Heat Gain Coefficient (SHGC)			
	1/4 Lite >410,	1/2 Lite >900,	3/4 Lite >1100,	Full Lite >1100,
2/A5/na/AIR/0.500				0.42 0.27
3/A5/na/AIR/0.188				0.40 0.24
3/A5/na/AIR/0.188				0.40 0.24
3/A5/na/AIR/0.188				0.40 0.20
2/A5/na/AIR/0.500			0.42 0.21	0.42 0.31
3/A5/na/AIR/0.188			0.40 0.28	0.39 0.35
3/A5/na/AIR/0.188			0.40 0.25	0.39 0.32

U-Factor

SHGC

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warranty the suitability of any product for any specific use. Consult manufacturer's literature for other product performance information.

* #glazing layers / spacer type / low-e emissivity (surface) / gap fill / gap width (na=not applicable)

**per NFRC 100 † square inches

www.nfrc.org